

Product information | TECHNICAL DATA SHEET

GLITTER VARNISH.

400 ml, 10.93 Oz, 310 g.

GENERAL DESCRIPTION

Fast drying, weather-resistant, water-based glitter varnish. Achieves an iridescent, flash-like effect on a multitude of supports such as iron, steel, plastic, wood and expanded polystyrene. It may be used indoors and in poorly ventilated spaces.

CHARACTERISTICS

- Water-based product.
- Acrylic.
- Cures well.
- Non-yellowing.
- Good adherence on all types of surfaces.
- For interior / exterior use.
- Easy to apply.

INSTRUCTIONS FOR USE

- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply on clean and dry surfaces. Remove corrosion with a wire brush. On plastics and polyesters, apply a suitable primer for better adhesion. Due to the multitude of materials and conditions for application, we recommend doing a prior test to verify that the product meets the requirements for each application.
- Apply in thin coats to obtain better results. Three thin coats are always better than one thick coat. Depending on the number of coats applied, the gloss finish may vary.
- Do not apply to plugged-in electronic equipment and use in well-ventilated areas.
- Request safety data sheets.

GENERAL DESCRIPTION

Binder type:	Acrylic
Color:	Transparent Silver, Transparent Gold, Transparent Multicolor
Gloss:	Gloss<90
Dry to the touch (ASTM D-1640 ISO 1517):	30'
Total dry time (ASTM D-1640 ISO 1517)	12 h
Theoretical performance (continuous painting):	3 m ²
Solvent:	Water and alcohol
Product life:	< 5 Years (Well Stored)
Heat resistance of paint:	100°C
Condition for application:	Minimum room temperature 8°C Surface temperature 5°-35 C Max humidity 85% R.H.P

CAUTION



APPLICATION

This product may be used on a multitude of surfaces including iron, steel, plastics, wood or directly on expanded polystyrene.

- Fine arts
- Industrial
- Crafts
- DIY
- Graffiti
- Decoration

APPEARANCE



LABEL



CAP SYSTEM



PACKAGING

Capacity 400 ml.
Packaging heat resistance: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm

